

Product Description:



Door Frame
The door frame is designed with the installer in mind. It has a simple to use hinge access, allowing installers to be hands-free when entering electrical compartment. This saves time and money.

Integrated Heatsink
Integrated cooling fin provides excellent thermal dissipation. This design allows the fixture to have extremely long lifetime hours.



Proprietary Optical Control
Specifically designed lens for freedom of layout design without any restraint. These optics are engineered for maximum light output.

Product Description:

The is a powerful luminaire that has been designed to meet a wide variety of locations. With the various mounting options it can be used as a flood light or as an area light. With the LEDs mounted on the large heatsink, the fixture can maintain a high lumen output while keeping the LED modules at a cool temperature.

Optional Kelvin color* with adder.

Features:

- LISTING**
UL and CUL listed for wet locations
- HOUSING**
Heavy duty die-cast aluminum powder coating, corrosion resistant hardware
- FINISH**
UV stabilized powder coated finish
- LENS**
Heat and impact PC Lens
- OPTIONS**
Wide / narrow distribution available with adder
Finish - Bronze. Color option with adder

Performance Data

Model NO.	System Watts	Lumens	LPW
WP-FC	104W	14127 lm**	135.8 lm/w
	120W	17719 lm**	147.6 lm/w

Specification:

Example: LED-3120

Model No.	System Watts	Input Voltage	CRI	Color Temp	Distribution	Option	Finish	Starting Temp
						Accessories		
WP-FC	104=104W	UNV=120-277V	7=70+	40=4000 K	T3=Type III	PE=Photocontrol EM=Emergency Driver	BZ=Bronze	-40°C
	120=120W			50=5000 K	T4=Type IV			

* Different LED Kelvin temperature available with 4-6 week lead time. Please call for a quote.

** DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to $\pm 10\%$.

Dimension:

