

VTPB4 LED Vaportight Poly-Body 4'



Fixture Dimensions: 51.37" x 6.40" x 4.75"

| Part ID | Wattage | Delivered Lumens | LPW |
|---------|---------|------------------|-----|
| 3500 | 23 | 3,404 | 149 |
| 5400 | 37 | 5,476 | 148 |
| 7000 | 47 | 6,956 | 148 |
| 11000 | 75 | 11,100 | 148 |

Delivered lumens based on 5000K CCT.

Ordering Information

| BAY | | VTPB4 | | DAC | |
|------------------------------|----------------------------|-------------------------------|-------------------|------------------------|--|
| Series | Family | Part ID | CCT | Lens Options | Voltage |
| 1st Source LED Bay Series | Vaportight Poly-Body 4' | 3500 5400 7000 11000 | 35K 40K 50K | DAC = Diffused Acrylic | U = Universal 120-277v 3 = 347v (Consult Factory) 4 = 480v (Consult Factory) |

| Dimming and Control Options | Accessories |
|-----------------------------|-------------|
|-----------------------------|-------------|

D0 = Dim to Off
 D10 = Dim to 10%
 DLV = Dim by Line Voltage
 MS = Motion Sensor
 Wireless Controls

C = Cord (Specify Length)
 P = Plug (Specify NEMA)
 EM = Emergency Driver

| | |
|---------|--------------|
| Project | |
| Type: | Approved By: |

APPLICATIONS

Food processing plants, breweries and bottling facilities, refrigerated storage, parking garages, roadway and pedestrian tunnels, etc.

CONSTRUCTION

UL 5VA fiberglass housing (will not burn or melt), suitable for outdoor use, entry holes for 1/2" NPT/M20 fittings (one or both ends), captive polycarbonate locking latches, 100% impact modified acrylic polycarbonate lens (linear ribbed diffusion), stainless steel mounting hardware clip for surface mount or chain hung applications

SYSTEM SPECIFICATIONS

High flux linear LED modules: 85 CRI, CCT: 3500K, 4000K or 5000K. Constant current LED power supplies: power factor > 0.9, THD < 20%, universal voltage 120-277v, 347-480v available.

DIMMING & CONTROLS

0-10v dimming, dim to off or dim by line voltage. Integral microwave motion sensor, wireless protocol from switch, PC or handheld device, A/B array switching, emergency driver battery back-up option.

RATINGS & WARRANTY

Temperature rated from -40°C to 38°C (-40°F to 100°F), service life > 100,000 hours (L90), IP65, CSA listed, BAA compliant.

(5) year product warranty. Consult factory for extended warranties.

