

RCxx14 LED Racquetball Court 1x4



Frame Out



Flange Mount

Lay-in model also available.

Lumen ID	CCT	Wattage	Delivered Lumens	LPW
12000	35K	84	10,649	127
12000	40K	84	10,746	128
12000	50K	84	11,254	134
17000	35K	118	14,473	123
17000	40K	118	14,904	126
17000	50K	118	15,881	135
19000	35K	139	16,476	120
19000	40K	139	17,394	125
19000	50K	139	17,412	125

Project	
Type:	Approved By:

APPLICATIONS

Racquetball, squash and handball courts. gymnasiums, multi-sport and recreational court facilities with recessed hard ceilings.

CONSTRUCTION

.040" white pre-painted aluminum, flush fit trim, obscured tempered glass lens, top access plate for quick power connection.

MOUNTING

Frame out mount (standard or narrow) or flange mount for recessed hard ceiling openings, lay-in for t-bar grid ceiling or existing frame.

SYSTEM SPECIFICATIONS

Hi flux linear LED modules, CRI > 80, CCT: 3500K, 4000K or 5000K. Constant current LED power supplies, power factor > 0.9, THD < 20%, universal voltage 120-277v, 347-480v available.

DIMMING & CONTROLS

0-10v dimming, dim to off or dim by line voltage. Integral microwave motion sensor, wireless protocol from switch, PC or handheld device, A/B array switching, emergency driver battery back-up option.

RATINGS & WARRANTY

Temperature rated from -28°C to 50°C (-20°F to 122°F), service life > 100,000 hours (L90). CSA listed, BAA compliant. Made in the USA. 5 year product warranty. Consult factory for extended warranties





Ordering Information

RSD						
Series	Housing	Lumen ID	CCT	Lens	Voltage	Dimming, EM, Controls
1st Source LED Recessed Series	RCFM14 = Frame Out RCFM14N = Frame Out Narrow RCFL14 = Flange Mount RCTB14 = Lay-In for T-Bar Grid Ceiling	12000 = 12,000 17000 = 17,000 19000 = 19,000	35K 40K 50K	OTG = Obscured Tempered Glass	U = 120-277v 3 = 347v 4 = 480v	D0 = Dim to Off D10 = Dim to 10% DLV = Dim by Line Voltage Emergency Drivers EM/2300 = 2,300L @ 16w EM/2900 = 2,900L @ 20w Controls (Consult Factory) Integrated Motion Sensor Daylight Harvesting A/B Array Switching Wireless Control System



Made in the USA





TITLE: RCFM14

3RD ANGLE PROJ: 

FILE LOCATION:
\\

UNLESS OTHERWISE NOTED:

SHEET: 1 of 1

SCALE: 1:12

SIZE:

UNITS:
INCHES

TOLERANCES:
.X $\pm .06$
.XX $\pm .03$
.XXX $\pm .010$
 $\angle \pm 1.0^\circ$

DRAWN BY: JMG

DATE: 6/29/2018

JO: XXXX

A

GD&T ASME
Y14.5M-1994

DWG #: RCFM14 DIMENSIONS




REV: N/C




1730 Industrial Drive, Auburn, CA 95603
(530) 887-1110 FAX (530) 887-0807
www.1stsourcelight.com


PROPRIETARY AND CONFIDENTIAL


THE INFORMATION CONTAINED IN THIS DRAWING
IS THE SOLE PROPERTY OF 1ST SOURCE LIGHTING.
ANY REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
1ST SOURCE LIGHTING IS PROHIBITED.









TITLE: RCFM14N				
3RD ANGLE PROJ: 		FILE LOCATION: \\		
UNLESS OTHERWISE NOTED:		SHEET: 1 of 1	SCALE: 1:12	
SIZE: A	UNITS: INCHES	DRAWN BY: JMG		DATE: 6/29/2018
	GD&T ASME Y14.5M-1994	DWG #: RCFM14N DIMENSIONS		JO: XXXX
TOLERANCES: .X ±.06 .XX ±.03 .XXX ±.010 < ±1.0°		REV: N/C		

RCFL14: 1x4 Flange Mount For Hard Ceiling



TITLE: RCFL14				
3RD ANGLE PROJ: 		FILE LOCATION: \\		
UNLESS OTHERWISE NOTED:		SHEET: 1 of 1	SCALE: 1:10	
SIZE: A	UNITS: INCHES GD&T ASME Y14.5M-1994	TOLERANCES: .X ±.06 .XX ±.03 .XXX ±.010 ≤ ±1.0°	DRAWN BY: JMG	DATE: 6/3/2019
DWG #: RCFL14 DIMENSIONS			REV: N/C	



TITLE: RCTB14			
3RD ANGLE PROJ: 		FILE LOCATION: \\	
UNLESS OTHERWISE NOTED:		SHEET:1 of 1	SCALE: 1:10
SIZE: A	UNITS: INCHES GD&T ASME Y14.5M-1994	TOLERANCES: .X ±.06 .XX ±.03 .XXX±.010 ≤ ±1.0°	DRAWN BY: JMG
		DATE: 6/29/2018	JO: XXXX
		DWG #: RCTB14 DIMENSIONS	REV: N/C