Source Lighting

LED Indoor Pickleball Court Light Direct-Indirect 4 or 8 Ft



Single or Tandem Mounting to Uni-Strut with Adjustable Angle Brackets

Length	Lumen ID	Wattage	Delivered Lumens	LPW
4'	19000	125	19,178	153
8'	38000	250	38,356	153

Fixture Dimensions

4 Ft: 46.25" x 3.25" x 3.8", Approx. 6 lbs 8 Ft: 93.50" x 3.25" x 3.8", Approx. 12 lbs

Ordering Information

	Approved Dyg	
ype:	Approved By:	

APPLICATIONS

Designed exclusively for indoor pickleball courts. Tri-directional 180 degree light output for wall-to-wall and floor to ceiling illumination.

CONSTRUCTION

.040" white pre-painted aluminum housing, power knockouts provided, linear diffused acrylic lens. All fixtures are manufactured in the USA.

MOUNTING

Standard mounting by unistrut provides maximum flexibility for mounting to a ceiling structure. Adjustable angle brackets allow for fixture aiming in 5 degree increments. 4 or 8 foot fixture lengths.

SYSTEM SPECIFICATIONS

High flux linear LED modules: 80+ CRI, CCT: 3500K, 4000K or 5000K. Constant current LED power supplies: power factor > 0.9, THD < 20%, universal voltage 120-277v, 347-480v available.

DIMMING & CONTROLS

Optional wireless dimming may be controlled by a remote switch, PC or handheld device. Standard dimming options are 0-10v low voltage (10%), dim to off (0%) or dim by line voltage.

RATINGS & WARRANTY

Temperature rated from -20° C to 50° C (-4° F to 122° F), service life > 100,000 hours (L90), CSA listed, 5 year product warranty.



