

LED Indoor Pickleball Court Light Direct-Indirect 4 or 8 Ft



Single or Tandem Mounting to Uni-Strut with Adjustable Angle Brackets

Length	Lumen ID	Wattage	Delivered Lumens	LPW
4'	19000	125	19,178	153
8'	38000	250	38,356	153

Fixture Dimensions

4 Ft: 46.25" x 3.25" x 3.8", Approx. 6 lbs 8 Ft: 93.50" x 3.25" x 3.8", Approx. 12 lbs

Ordering Information

BAY	Series	Length	Arrays	Lumen ID	CCT	Lens Options	Voltage
	1st Source LED Bay Series	LHB4 = 4 Ft LHB8 = 8 Ft	3 6	19000 38000	40K 50K	DAC = Diffused Acrylic	U = Universal 120-277v 3 = 347v (Consult Factory) 4 = 480v (Consult Factory)
Mounting Options		Dimming			Controls		
ABM = Angle Bracket Mount Consult Factory For Additional Mounting Options		D0 = Dim to Off (0%) D10 = Dim to 10% DLV = Dim by Line Voltage			Consult Factory for Wireless Control Options		

Project	
Type:	Approved By:

APPLICATIONS

Designed exclusively for indoor pickleball courts. Tri-directional 180 degree light output for wall-to-wall and floor to ceiling illumination.

CONSTRUCTION

.032" white pre-painted aluminum housing, power knockouts provided, linear diffused acrylic lens. All fixtures are manufactured in the USA.

MOUNTING

Standard mounting by unistrut provides maximum flexibility for mounting to a ceiling structure. Adjustable angle brackets allow for fixture aiming in 5 degree increments. 4 or 8 foot fixture lengths.

SYSTEM SPECIFICATIONS

High flux linear LED modules: 80+ CRI, CCT: 3500K, 4000K or 5000K. Constant current LED power supplies: power factor > 0.9, THD < 20%, universal voltage 120-277v, 347-480v available.

DIMMING & CONTROLS

Optional wireless dimming may be controlled by a remote switch, PC or handheld device. Standard dimming options are 0-10v low voltage (10%), dim to off (0%) or dim by line voltage.

RATINGS & WARRANTY

Temperature rated from -20°C to 50°C (-4°F to 122°F), service life > 100,000 hours (L90), CSA listed, 5 year product warranty.